

SANYO	No.2479A	2SA1607/2SC4168
		PNP/NPN Epitaxial Planar Silicon Transistors High-Speed Switching Applications

Features

- Fast switching speed
- High gain-bandwidth product
- Low saturation voltage

() : 2SA1607

Absolute Maximum Ratings at Ta = 25°C

			unit
Collector to Base Voltage	V_{CB0}	(-)40	V
Collector to Emitter Voltage	V_{CE0}	(-)20	V
Emitter to Base Voltage	V_{EB0}	(-)5	V
Collector Current	I_C	(-)150	mA
Collector Current(Pulse)	I_{CP}	(-)300	mA
Base Current	I_B	(-)30	mA
Collector Dissipation	P_C	200	mW
Junction Temperature	T_j	150	°C
Storage Temperature	T_{stg}	-55 to +150	°C

Electrical Characteristics at Ta = 25°C

			min	typ	max	unit
Collector Cutoff Current	I_{CBO}	$V_{CB} = (-)30V, I_E = 0$			(-)0.1	μA
Emitter Cutoff Current	I_{EBO}	$V_{EB} = (-)4V, I_C = 0$			(-)0.1	μA
DC Current Gain	h_{FE}	$V_{CE} = (-)1V, I_C = (-)10mA$	60*		270*	
					(180)	
Gain-Bandwidth Product	f_T	$V_{CE} = (-)10V, I_C = (-)10mA$		700		MHz
				(400)		
Output Capacitance	c_{ob}	$V_{CB} = (-)10V, f = 1MHz$		(2.9)2.6		pF
C-E Saturation Voltage	$V_{CE(sat)}$	$I_C = (-)10mA, I_B = (-)1mA$		0.08	(-)0.2	V
				(-0.07)		
B-E Saturation Voltage	$V_{BE(sat)}$	$I_C = (-)10mA, I_B = (-)1mA$		0.72	(-)1.0	V
				(-0.75)		
C-B Breakdown Voltage	$V_{(BR)CBO}$	$I_C = (-)10μA, I_E = 0$	(-)40			V
C-E Breakdown Voltage	$V_{(BR)CEO}$	$I_C = (-)1mA, R_{BE} = ∞$	(-)20			V
E-B Breakdown Voltage	$V_{(BR)EBO}$	$I_E = (-)10μA, I_C = 0$	(-)5			V

Continued on next page.


* : The 2SA1607/2SC4168 are classified by 10mA h_{FE} as follows :

2SA1607	60	3	120	90	4	180
2SC4168	60	3	120	90	4	180
				135	5	270

Marking 2SA1607 : YL
 2SC4168 : GT
 h_{FE} rank 2SA1607 : 3,4
 2SC4168 : 3,4,5

Package Dimensions 2018A

(unit : mm)




2SA1607/2SC4168







Continued from preceding page.

			min	typ	max	unit
Delay Time	t_d	See specified Test Circuit.		(14)11	20	ns
Rise Time	t_r	"		(11)10	20	ns
Storage Time	t_{stg}	"		(80)70	180	ns
Fall Time	t_f	"		(16)15	25	ns









Switching Time Test Circuit






$I_{B1} = -I_{B2} = I_C = 50mA$



2SA1607/2SC4168





- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
 - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use:
 - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.