DATA SHEET

NEC

MOS FIELD EFFECT TRANSISTOR

2SK1273

N-CHANNEL MOS FET
FOR HIGH SPEED SWITCHING

PACKAGE DIMENSIONS (Unit : mm)



1.Source
2.Drain
3.Gate
MARK:NA



(Diode in the figure is the parasitic diode.)

The 2SK1273, N-channel vertical type MOS FET, is a switching device which can be driven directly by the output of ICs having a 5 V power source.

As the MOS FET has low on-state resistance and excellent switching characteristics, it is suitable for driving actuators such as motors, relays, and solenoids.

FEATURES

- Directly driven by ICs having a 5 V power source.
- Has low on-state resistance
  $R_{DS(on)}$ = 1.00 Ω MAX. @V_{GS} = 4.0 V, I_D = 0.5 A
  $R_{DS(on)}$ = 0.65 Ω MAX. @V_{GS} = 10 V, I_D = 0.5 A
- Not necessary to consider driving current because of its high input impedance.
- Possible to reduce the number of parts by omitting the bias resistor.

QUALITY GRADE

Standard

Please refer to "Quality grade on NEC Semiconductor Devices" (Document number IEI-1209) published by NEC Corporation to know the specification of quality grade on the devices and its recommended applications.

ABSOLUTE MAXIMUM RATINGS (T_a = 25 °C)

PARAMETER	SYMBOL	RATINGS	UNIT	TEST CONDITIONS
Drain to Source Voltage	V_{DSS}	60	V	V_{GS} = 0
Gate to Source Voltage	V_{GSS}	±20	V	V_{DS} = 0
Drain Current	$I_{D(DC)}$	±2.0	A	
Drain Current	$I_{D(pulse)}$	±4.0	A	PW ≦ 10 ms, Duty Cycle ≦ 50 %
Total Power Dissipation	P_T	2.0	W	when using ceramic board of 16 cm² x 0.7 mm
Channel Temperature	T_{ch}	150	°C	
Storage Temperature	T_{stg}	−55 to +150	°C	

Document No. TC−2340A
(O.D.No. TC−7793B)
Date Published November 1994 M
Printed in Japan

© NEC Corporation 1991

ELECTRICAL CHARACTERISTICS (T_a = 25 °C)

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITIONS
Drain Cut-off Current	I_{DSS}			10	μA	V_{DS} = 60 V, V_{GS} = 0
Gate Leakage Current	I_{GSS}			±10	μA	V_{GS} = ±20 V, V_{DS} = 0
Gate Cut-off Voltage	$V_{GS(off)}$	1.0	1.7	2.5	V	V_{DS} = 10 V, I_D = 1 mA
Forward Transfer Admittance	$\|y_{fs}\|$	0.4			S	V_{DS} = 10 V, I_D = 0.5 A
Drain to Source On-State Resistance	$R_{DS(on)1}$		0.31	1.00	Ω	V_{GS} = 4.0 V, I_D = 0.5 A
Drain to Source On-State Resistance	$R_{DS(on)2}$		0.24	0.65	Ω	V_{GS} = 10 V, I_D = 0.5 A
Input Capacitance	C_{iss}		220		pF	V_{DS} = 10 V, V_{GS} = 0, f = 1 MHz
Output Capacitance	C_{oss}		105		pF	
Feedback Capacitance	C_{rss}		16		pF	
Turn-On Delay Time	$t_{d(on)}$		15		ns	$V_{GS(on)}$ = 10 V, R_G = 10 Ω V_{DD} = 25 V, I_D = 0.5 A R_L = 50 Ω
Rise Time	t_r		35		ns	
Turn-Off Delay Time	$t_{d(off)}$		380		ns	
Fall Time	t_f		120		ns	

SWITCHING TIME MEASUREMENT CIRCUIT AND CONDITIONS





TYPICAL CHARACTERISTICS (T_a = 25 °C)

DERATING FACTOR OF FORWARD BIAS SAFE OPERATING AREA



FORWARD BIAS SAFE OPERATING AREA



TOTAL POWER DISSIPATION vs. AMBIENT TEMPERATURE



DRAIN CURRENT vs. DRAIN TO SOURCE VOLTAGE



TRANSFER CHARACTERISTICS



GATE TO SOURCE CUTOFF VOLTAGE vs. CHANNEL TEMPERATURE



FORWARD TRANSFER ADMITTANCE vs. DRAIN CURRENT



DRAIN TO SOURCE ON-STATE RESISTANCE vs. GATE TO SOURCE VOLTAGE



DRAIN TO SOURCE ON-STATE RESISTANCE vs. DRAIN CURRENT



DRAIN TO SOURCE ON-STATE RESISTANCE vs. DRAIN CURRENT



DRAIN TO SOURCE ON-STATE RESISTANCE vs. DRAIN CURRENT



CAPACITANCE vs. DRAIN TO SOURCE VOLTAGE



SWITCHING CHARACTERISTICS



SOURCE TO DRAIN DIODE FORWARD VOLTAGE



RECOMMENDED SOLDERING CONDITIONS

Mounting of this product by soldering should be done under the following conditions.
Please consult our representatives about soldering methods and conditions other than these.

SURFACE MOUNT TYPE

For details of the recommended soldering conditions, see the information document.
"Device Mounting Manual for Surface Mounting (IEI-1207)."

Soldering Method	Soldering Conditions	Symbol for Recommended Conditions
Infrared Reflow	Package peak temp.: 230 °C Soldering time: within 30 sec (above 210 °C) Soldering times: 1, Days limitation: none*	IR30-00
Vapor Phase Soldering	Package peak temp.: 215 °C Soldering time: within 40 sec (above 200 °C) Soldering times: 1, Days limitation: none*	VP15-00
Wave Soldering	Soldering bath temp.: below 260 °C Soldering time: within 10 sec Soldering times: 1, Days limitation: none*	WS60-00

*: Stored days under storage conditions at 25 °C and below 65 % R.H. after the dry-pack has been opened.

Note 1 Combination of soldering methods should be avoided.

REFERENCE

Document Name	Document No.
NEC semiconductor device reliability/quality control system.	TEI-1202
Quality grade on NEC semiconductor devices.	IEI-1209
Semiconductor device mounting technology manual.	IEI-1207
Semiconductor device package manual.	IEI-1213
Guide to quality assurance for semiconductor devices.	MEI-1202
Semiconductor selection guide.	MF-1134

(MEMO)

No part of this document may be copied or reproduced in any form or by any means without the prior written consent of NEC Corporation. NEC Corporation assumes no responsibility for any errors which may appear in this document.
NEC Corporation does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from use of a device described herein or any other liability arising from use of such device. No license, either express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC Corporation or others.
The devices listed in this document are not suitable for use in aerospace equipment, submarine cables, nuclear reactor control systems and life support systems. If customers intend to use NEC devices for above applications or they intend to use "Standard" quality grade NEC devices for applications not intended by NEC, please contact our sales people in advance.
Application examples recommended by NEC Corporation
Standard: Computer, Office equipment, Communication equipment, Test and Measurement equipment, Machine tools, Industrial robots, Audio and Visual equipment, Other consumer products, etc.
Special: Automotive and Transportation equipment, Traffic control systems, Antidisaster systems, Anticrime systems, etc.

M4 92.6