



on-chip resistor PNP silicon epitaxial transistor
For mid-speed switching

FEATURES

- Up to 2A high current drives such as IC outputs and actuators available
- On-chip bias resistor
- Low power consumption during drive



PACKAGE DRAWING (UNIT: mm)



Electrode Connection

E: Emitter

C: Collector (Fin)

B: Base

HR1 SERIES LISTS

Products	Marking	R ₁ (KΩ)	R ₂ (KΩ)
HR1A3M	MP	1.0	1.0
HR1F3P	MQ	2.2	10
HR1L3N	MR	4.7	10
HR1A4,	MS	10	10
HR1L2Q	MT	0.47	4.7
HR1F2Q	MU	0.22	2.2
HR1A4A	MX	—	10

ABSOLUTE MAXIMUM RATINGS (Ta = 25°C)

Parameter	Symbol	Ratings	Unit
Collector to base voltage	V _{CBO}	−60	V
Collector to emitter voltage	V _{CEO}	−60	V
Emitter to base voltage	V _{EBO}	−10	V
Collector current (DC)	I _{C(DC)}	−1.0	A
Collector current (Pulse)	I _{C(pulse)} *	−2.0	A
Base current (DC)	I _{B(DC)}	−0.02	A
Total power dissipation	P _T **	2.0	W
Junction temperature	T _J	150	°C
Storage temperature	T _{stg}	−55 to +150	°C

* PW ≤ 10 ms, duty cycle ≤ 50 %

** When 0.7 mm × 16 cm² ceramic board is used

The information in this document is subject to change without notice. Before using this document, please confirm that this is the latest version.
Not all devices/types available in every country. Please check with local NEC representative for availability and additional information.

HR1A3M

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Collector cutoff current	I_{CBO}	$V_{CB} = -60\text{ V}, I_E = 0$			-100	nA
DC current gain	h_{FE1}^{**}	$V_{CE} = -2.0\text{ V}, I_C = -0.1\text{ A}$	50			—
DC current gain	h_{FE2}^{**}	$V_{CE} = -2.0\text{ V}, I_C = -0.5\text{ A}$	100			—
DC current gain	h_{FE3}^{**}	$V_{CE} = -2.0\text{ V}, I_C = -1.0\text{ A}$	50			—
Low level output voltage	V_{OL}^{**}	$V_{IN} = -5.0\text{ V}, I_C = -0.4\text{ A}$			-0.4	V
Low level input voltage	V_{IL}^{**}	$V_{CE} = -5.0\text{ V}, I_C = -100\text{ }\mu\text{A}$			-0.3	V
Input resistance	R_1		0.7	1.0	1.3	k Ω
E-to-B resistance	R_2		0.7	1.0	1.3	k Ω

** PW \leq 350 μs , duty cycle \leq 2 %

HR1F3P

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Collector cutoff current	I_{CBO}	$V_{CB} = -60\text{ V}, I_E = 0$			-100	nA
DC current gain	h_{FE1}^{**}	$V_{CE} = -2.0\text{ V}, I_C = -0.1\text{ A}$	150			—
DC current gain	h_{FE2}^{**}	$V_{CE} = -2.0\text{ V}, I_C = -0.5\text{ A}$	100			—
DC current gain	h_{FE3}^{**}	$V_{CE} = -2.0\text{ V}, I_C = -1.0\text{ A}$	50			—
Low level output voltage	V_{OL}^{**}	$V_{IN} = -5.0\text{ V}, I_C = -0.3\text{ A}$			-0.3	V
Low level input voltage	V_{IL}^{**}	$V_{CE} = -5.0\text{ V}, I_C = -100\text{ }\mu\text{A}$			-0.3	V
Input resistance	R_1		1.54	2.2	2.86	k Ω
E-to-B resistance	R_2		7	10	13	k Ω

** PW \leq 350 μs , duty cycle \leq 2 %

HR1L3N

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Collector cutoff current	I_{CBO}	$V_{CB} = -60\text{ V}, I_E = 0$			-100	nA
DC current gain	h_{FE1}^{**}	$V_{CE} = -2.0\text{ V}, I_C = -0.1\text{ A}$	150			—
DC current gain	h_{FE2}^{**}	$V_{CE} = -2.0\text{ V}, I_C = -0.5\text{ A}$	100			—
DC current gain	h_{FE3}^{**}	$V_{CE} = -2.0\text{ V}, I_C = -1.0\text{ A}$	50			—
Low level output voltage	V_{OL}^{**}	$V_{IN} = -5.0\text{ V}, I_C = -0.2\text{ A}$			-0.3	V
Low level input voltage	V_{IL}^{**}	$V_{CE} = -5.0\text{ V}, I_C = -100\text{ }\mu\text{A}$			-0.3	V
Input resistance	R_1		3.29	4.7	6.11	k Ω
E-to-B resistance	R_2		7	10	13	k Ω

** PW \leq 350 μs , duty cycle \leq 2 %

HR1A4M

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Collector cutoff current	I _{CBO}	V _{CB} = -60 V, I _E = 0			-100	nA
DC current gain	h _{FE1} **	V _{CE} = -2.0 V, I _C = -0.1 A	150			—
DC current gain	h _{FE2} **	V _{CE} = -2.0 V, I _C = -0.5 A	100			—
DC current gain	h _{FE3} **	V _{CE} = -2.0 V, I _C = -1.0 A	50			—
Low level output voltage	V _{OL} **	V _{IN} = -5.0 V, I _C = -0.1 A			-0.2	V
Low level input voltage	V _{IL} **	V _{CE} = -5.0 V, I _C = -100 μA			-0.3	V
Input resistance	R ₁		7	10	13	kΩ
E-to-B resistance	R ₂		7	10	13	kΩ

** PW ≤ 350 μs, duty cycle ≤ 2 %

HR1L2Q

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Collector cutoff current	I _{CBO}	V _{CB} = -60 V, I _E = 0			-100	nA
DC current gain	h _{FE1} **	V _{CE} = -2.0 V, I _C = -0.1 A	150			—
DC current gain	h _{FE2} **	V _{CE} = -2.0 V, I _C = -0.5 A	100			—
DC current gain	h _{FE3} **	V _{CE} = -2.0 V, I _C = -1.0 A	50			—
Low level output voltage	V _{OL} **	V _{IN} = -5.0 V, I _C = -0.5 A			-0.55	V
Low level input voltage	V _{IL} **	V _{CE} = -5.0 V, I _C = -100 μA			-0.3	V
Input resistance	R ₁		329	470	611	Ω
E-to-B resistance	R ₂		3.29	4.7	6.11	kΩ

** PW ≤ 350 μs, duty cycle ≤ 2 %

HR1F2Q

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Collector cutoff current	I _{CBO}	V _{CB} = -60 V, I _E = 0			-100	nA
DC current gain	h _{FE1} **	V _{CE} = -2.0 V, I _C = -0.1 A	100			—
DC current gain	h _{FE2} **	V _{CE} = -2.0 V, I _C = -0.5 A	100			—
DC current gain	h _{FE3} **	V _{CE} = -2.0 V, I _C = -1.0 A	50			—
Low level output voltage	V _{OL} **	V _{IN} = -5.0 V, I _C = -0.5 A			-0.55	V
Low level input voltage	V _{IL} **	V _{CE} = -5.0 V, I _C = -100 μA			-0.3	V
Input resistance	R ₁		154	220	286	kΩ
E-to-B resistance	R ₂		1.54	2.2	2.86	kΩ

** PW ≤ 350 μs, duty cycle ≤ 2 %





HR1A4A

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Collector cutoff current	I_{CBO}	$V_{CB} = -60\text{ V}$, $I_E = 0$			-100	nA
DC current gain	h_{FE1}^{**}	$V_{CE} = -2.0\text{ V}$, $I_C = -0.1\text{ A}$	150			—
DC current gain	h_{FE2}^{**}	$V_{CE} = -2.0\text{ V}$, $I_C = -0.5\text{ A}$	100			—
DC current gain	h_{FE3}^{**}	$V_{CE} = -2.0\text{ V}$, $I_C = -1.0\text{ A}$	50			—
Collector saturation voltage	$V_{CE(sat)}^{**}$	$I_C = -500\text{ mA}$, $I_B = -10\text{ mA}$		0.20	0.35	V
Low level input voltage	V_{IL}^{**}	$V_{CE} = -5.0\text{ V}$, $I_C = -100\text{ }\mu\text{A}$	-0.3		-1.5	V
Input resistance	R_1		—	—	—	Ω
E-to-B resistance	R_2		7	10	13	k Ω

** PW $\leq 350\text{ }\mu\text{s}$, duty cycle $\leq 2\%$

TYPICAL CHARACTERISTICS ($T_a = 25^\circ\text{C}$)



- **The information in this document is current as of July, 2001. The information is subject to change without notice. For actual design-in, refer to the latest publications of NEC's data sheets or data books, etc., for the most up-to-date specifications of NEC semiconductor products. Not all products and/or types are available in every country. Please check with an NEC sales representative for availability and additional information.**
- No part of this document may be copied or reproduced in any form or by any means without prior written consent of NEC. NEC assumes no responsibility for any errors that may appear in this document.
- NEC does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from the use of NEC semiconductor products listed in this document or any other liability arising from the use of such products. No license, express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC or others.
- Descriptions of circuits, software and other related information in this document are provided for illustrative purposes in semiconductor product operation and application examples. The incorporation of these circuits, software and information in the design of customer's equipment shall be done under the full responsibility of customer. NEC assumes no responsibility for any losses incurred by customers or third parties arising from the use of these circuits, software and information.
- While NEC endeavours to enhance the quality, reliability and safety of NEC semiconductor products, customers agree and acknowledge that the possibility of defects thereof cannot be eliminated entirely. To minimize risks of damage to property or injury (including death) to persons arising from defects in NEC semiconductor products, customers must incorporate sufficient safety measures in their design, such as redundancy, fire-containment, and anti-failure features.
- NEC semiconductor products are classified into the following three quality grades:
 "Standard", "Special" and "Specific". The "Specific" quality grade applies only to semiconductor products developed based on a customer-designated "quality assurance program" for a specific application. The recommended applications of a semiconductor product depend on its quality grade, as indicated below. Customers must check the quality grade of each semiconductor product before using it in a particular application.
 "Standard": Computers, office equipment, communications equipment, test and measurement equipment, audio and visual equipment, home electronic appliances, machine tools, personal electronic equipment and industrial robots
 "Special": Transportation equipment (automobiles, trains, ships, etc.), traffic control systems, anti-disaster systems, anti-crime systems, safety equipment and medical equipment (not specifically designed for life support)
 "Specific": Aircraft, aerospace equipment, submersible repeaters, nuclear reactor control systems, life support systems and medical equipment for life support, etc.
 The quality grade of NEC semiconductor products is "Standard" unless otherwise expressly specified in NEC's data sheets or data books, etc. If customers wish to use NEC semiconductor products in applications not intended by NEC, they must contact an NEC sales representative in advance to determine NEC's willingness to support a given application.
 (Note)
 (1) "NEC" as used in this statement means NEC Corporation and also includes its majority-owned subsidiaries.
 (2) "NEC semiconductor products" means any semiconductor product developed or manufactured by or for NEC (as defined above).