

# MA2ZV01

## Silicon epitaxial planar type


For VCO

### ■ Features

- Good linearity and large capacitance-ratio in  $C_D$  —  $V_R$  relation
- Small series resistance  $r_D$
- S-mini type package, allowing downsizing of equipment and automatic insertion through the taping package

### ■ Absolute Maximum Ratings $T_a = 25^\circ\text{C}$

| Parameter            | Symbol    | Rating      | Unit             |
|----------------------|-----------|-------------|------------------|
| Reverse voltage (DC) | $V_R$     | 6           | V                |
| Junction temperature | $T_j$     | 150         | $^\circ\text{C}$ |
| Storage temperature  | $T_{stg}$ | -55 to +150 | $^\circ\text{C}$ |



Marking Symbol: 7X

### ■ Electrical Characteristics $T_a = 25^\circ\text{C}$

| Parameter            | Symbol                | Conditions                              | Min  | Typ | Max  | Unit     |
|----------------------|-----------------------|-----------------------------------------|------|-----|------|----------|
| Reverse current (DC) | $I_R$                 | $V_R = 6\text{ V}$                      |      |     | 10   | nA       |
| Diode capacitance    | $C_{D(1V)}$           | $V_R = 1\text{ V}, f = 1\text{ MHz}$    | 15.0 |     | 17.0 | pF       |
|                      | $C_{D(3V)}$           | $V_R = 3\text{ V}, f = 1\text{ MHz}$    | 5.0  |     | 7.0  | pF       |
| Capacitance ratio    | $C_{D(1V)}/C_{D(3V)}$ |                                         | 2.2  |     |      | —        |
| Series resistance*   | $r_D$                 | $C_D = 9\text{ pF}, f = 470\text{ MHz}$ |      |     | 1.0  | $\Omega$ |

Note) 1. Rated input/output frequency: 470 MHz

2. \*:  $r_f$  measuring instrument: YHP MODEL 4191A RF IMPEDANCE ANALYZER

