

Zener diode

FTZ5.6E

● Applications

Noise suppression on signal line
Constant voltage control


● Features

- 1) Small surface mounting type.(SMD5)
- 2) High reliability.
- 3) Multiple diodes with common anode configuration.

● Construction

Silicon epitaxial planar

● External dimensions (Units: mm)



● Absolute maximum ratings ($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Limits	Unit
Power dissipation	P^*	200	mW
Junction temperature	T_j	125	°C
Storage temperature	T_{stg}	-55 ~ +125	°C

* Total of 4 elements

● Electrical characteristics ($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Zener voltage	V_z	5.31	5.6	5.92	V	$I_z = 5\text{mA}$
Reverse current	I_R	-	-	1	μA	$V_R = 2.5\text{V}$
Operating resistance	Z_z	-	-	60	Ω	$I_z = 5\text{mA}$
Rising operating resistance	Z_{zk}	-	-	200	Ω	$I_z = 0.5\text{mA}$

Diodes

●High voltage performance

Item	Standard 1	IEC - 1000 - 4 - 2
Device configuration	Charge/discharge capacitance : 200 pF ± 10% Discharge resistance : 400 Ω ± 10%	Charge/discharge capacitance : 150 pF Discharge resistance : 330 Ω
Judgment contents	5 repetitions No spark or smoke emitted : ± 25 kV No element destruction : ± 20 kV No malfunction : ± 8 kV	10 repetitions No malfunction Contact : ± 8 kV Suspended : ± 15 kV

●Electrical characteristic curve (Ta = 25°C)




Fig. 1 Derating curve

ROHM

■ 7828999 0024527 543 ■

171041