

**SURFACE MOUNT  
SCHOTTKY BARRIER RECTIFIERS**

REVERSE VOLTAGE - 20 Volts  
FORWARD CURRENT - 1.0 Ampere


**FEATURES**

- For surface mounted applications
- Metal-Semiconductor junction with guardring
- Epitaxial construction
- Low VF&IR provides higher efficiency and extends battery life
- Plastic material has UL flammability classification 94V-0
- For use in portable and battery powered product
- Typical applications are ac/ac and dc/dc converters, reverse battery protection, and "Oring" of multiple supply voltage

**MECHANICAL DATA**

- Case : JEDEC DO-216AA Molded plastic
- Polarity : Cathode designated by TAB 1
- Approx Weight : 0.016grams
- Mounting position : Any

**DO-216AA**



**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

Ratings at 25°C ambient temperature unless otherwise specified.

Characteristics	Symbol	MB120E		Units
Maximum recurrent peak reverse voltage	V <sub>rrm</sub>	20		V
Maximum RMS voltage	V <sub>rms</sub>	14		V
Maximum DC blocking voltage	V <sub>DC</sub>	20		V
Maximum average forward rectified current @ T <sub>L</sub> =130°C	I <sub>(AV)</sub>	1.0		A
Peak forward surge current 8.3 ms single half-sine-wave superimposed on rated load (JEDEC Method)	I <sub>FSM</sub>	50		A
Maximum instantaneous forward voltage (Note 1) ( @ I <sub>F</sub> =0.1A ) ( @ I <sub>F</sub> =1.0A ) ( @ I <sub>F</sub> =2.0A )	V <sub>F</sub>	@ T <sub>J</sub> = 25°C	@ T <sub>J</sub> = 100°C	V
		0.455	0.360	
		0.530	0.455	
Maximum instantaneous reverse current ( @ V <sub>R</sub> =20V ) ( @ V <sub>R</sub> =10V ) ( @ V <sub>R</sub> = 5V )	I <sub>R</sub>	@ T <sub>J</sub> = 25°C	@ T <sub>J</sub> = 100°C	uA
		10	1600	
		1.0	500	
		0.5	300	
Thermal resistance - Junction to Lead (Anode)	R <sub>thj</sub>	35		°C/W
Thermal resistance - Junction to Tab (Cathode)	R <sub>thtab</sub>	20		
Thermal resistance - Junction to Ambient	R <sub>thja</sub>	250		
Operating Temperature Range	T <sub>J</sub>	-55 to +150		°C
Storage Temperature Range	T <sub>STG</sub>	-55 to +150		°C

NOTE: 1.Pulse Test: Pulse Width = 300us , Duty Cycle = 2%

REV. 1, Oct-2010, KSHP03

Fig.1 - Forward Current Derating Curve




Fig.2 - Typical Reverse Characteristics




Fig.3 - Maxmun Non-Repetitive Peak Forward Surge Current




Fig.4 - Typical Junction Capacitance






Fig.5 - Typical Forward Characteristics



FOOTPRINTS FOR SOLDERING



## **Important Notice and Disclaimer**

LSC reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

LSC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does LSC assume any liability for application assistance or customer product design. LSC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of LSC.

LSC products are not authorized for use as critical components in life support devices or systems without express written approval of LSC.