




产品特点 FEATURES

- 小型、超薄式 (3.2×2.5×0.7 mm) Small size and ultra-thin
- 宽温度范围应用 (-40℃~85℃) Wide operating temperature range
- 贴片、无铅 SMD Leadless
- 金属密封，具有高可靠性能 Metal seam sealing reaches high reliability



标准规格 STAND SPECIFICATIONS

频率范围 (F0) Frequency Range (F0)	10.000~48.000 MHz
振荡模式 Overtone Order	Fundamental
频率公差 Frequency Tolerance (at 25℃)	±20ppm Typical (tighter tolerance is available)
频率温度特性 Frequency Temperature Stability	±20ppm Typical (tighter tolerance is available)
工作温度范围 Operating Temperature Range	-20℃~+70℃ (other operating range is available)
储存温度范围 Storage Temperature Range	-40℃ ~ +125℃
静态电容 Shunt Capacitance (C0)	4.0pf Max
等效电阻 Equivalent Series Resistance	refer to ESR Table
驱动电平 Drive Level	0.01uW ~100uW
负载电容 Load Capacitance	8pf ~ 32pf
年老化 Ageing (at 25℃)	3ppm/ year Max


等效电阻 ESR

Fundamental	
10.000~19.999MHz	80 Ω Max
20.000~26.999MHz	60 Ω Max
27.000~48.000MHz	50 Ω Max


Note: Specified a product with specification is welcome, please contact our sales representative.

注：可按客户参数要求定制产品。

外形尺寸 DIMENSIONS



回流焊 REFLOW CONDITION



使用须知 NOTICE FOR USE

The content given above in this data sheet might be updated without prior notice. If you don't have an advance notice, please confirm with our sales.

在没有通知的情况下，以上产品可能会更新升级。请联系我们了解具体的相关产品。